

# DHI-ASF280B

## Magnetic Lock



- 280KG \* 2 Anti-pull.
- Built-in reverse current protection device(MOV).
- Aluminum shell with high strength alloy material.
- Electromagnetic suction work completely, there is no mechanical failure.
- Can be set DC12V or DC24V.
- The residual magnetic design proof, wear materials.
- Double lock body insulation treatment.
- Supports door detector signal feedback.

### Technical Specification

#### Basic

Suction Plate Dimensions	180 mm × 38 mm × 11 mm (7.09" × 1.50" × 0.43")
Applicable Door Type	Wooden door, glass door, metal door, fire door, etc

#### Function

Signal Output	Door status feed back
Security	Open while power off

#### General

Net Weight	4 Kg (8.82 lb)
Accessory	280 L; 280 U; 280 ZL
Starting Current	480 mA × 2; 240 mA × 2
Power Supply	12 VDC; 24 VDC
Lock Dimensions	500 mm × 47 mm × 26 mm (19.69" × 1.85" × 1.02")
Operating Temperature	-30 °C to +60 °C (-22 °F to +140 °F)
Operating Humidity	≤ 95%

### Ordering Information

Type	Model	Description
ASF Series	DHI-ASF280B	Magnetic Lock

### Dimensions (mm[inch])

