

DHI-LM55-S200

55" FHD Monitor



Features:

- Suitable for continuous 24/7 operation
- Using tamper-proof metal housing
- 6ms response time for no motion blur, judder or ghosting
- High fidelity digital processing for a brilliant and vivid video
- 178°/178° wide uninterrupted viewing angle
- Professional thermal design to extend equipment lifespan
- Built-in speakers, low energy consumption
- Support multiple signals, such as HDMI, VGA, USB multimedia, Audio, RS232



Technical Specification

Model

Model	DHI-LM55-S200
-------	---------------

Display

Screen Size	54.6"
Aspect Ratio	16:9
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance	350cd/m ²
Contrast	1200:1
Display Color	16.7M(8bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response time	6ms
Refresh Rate	60Hz

Signals

Input	HDMI×1, VGA(D-Sub)×1, USB multimedia×1, Audio in×1, RS232(RJ45)×1	
Output	Audio out×1, RS232(RJ45)×1	
	Speaker	5W×2

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz, 2.5A
--------------	-------------------------------------

Consumption (Standard)	140W	
Consumption (Standby)	≤0.5W	
Type	Internal	
Net Weight	15kg (33.1lb)	
Gross Weight	18.6kg (41.0lb)	
Bezel Width	13.9mm (U/L/R/B)	
Wall Mount	400×400mm (15.7"×15.7")	
Dimension without standard (W×H×D)	1243.2×714×69.6mm (48.9"×28.1"×2.7")	
Package(W×H×D)	1364×824×154mm(53.7"×32.4"×6.1")	
Work Environment	Temperature	0℃~40℃ (32°F~104°F)
	Humidity	20%~85%

Accessory

Standard	HDMI cable, Power cable, Hanging bracket, Remote control
Optional	Pedestal

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

